# BS Copper



The **BS Copper** pushbutton, fitted with an untreated copper face, is a self-cleaning solution to the commonly touched elevator surface. Buttons can be paired with a large selection of braille tags to combine aesthetics and functionality.

#### ✓ Naturally Self-Cleaning Button

- ✓ Vandal-proof
- Perfect retrofit product: Replace on the Pressel only, contact & wiring unchanged.
- ✓ LED Illumination available in Red, Green, Blue, White & Amber

SS#4 COP shown with 7" Giotto PI, BS Copper pushbutton, Julius Surround non-illuminated tactile.

## Variety of Tactile Combinations











#### **General Details**

General: Vandal-proof Studless Frontal Mounting Copper Pushbutton. Fastened by jam-nut on plates from 11 to 22 Gauge thick.
Pressel: AISI 303 turned Stainless Steel with Untreated Copper Insert. Pressel activation is limited by Stainless Steel base in Pressel. This prevents any stress on contact block resulting in an extremely robust vandal-proof pushbutton.
Contacts: Available with one or two microswitch(es)
Wiring: Screw terminals or JST Pin Connector

Voltage: Multivolt: 6V to 120V AC/DC, 24V AC/DC


Illumination: LED-illumination of target in Red, Green, Blue, White and Amber


Stroke: 0.040"

Avg. Life: 1,500,000 activations


Degree of protection: IP54

#### Physical Characteristics





## Mounting Requirements




### **Component Ordering Information**

#### Complete Assembley BSRCFXXXX.00

Contact 0 - No Contact 3 - 1 Contact (Microswitch) 4 - 2 Contact (Microswitch)

Voltage 4 - 24V AC/DC M - Multivolt 6V-120V AC/DC 0 - No Illumination Illumination 0 - No Illumination A - Amber B - Blue R - Red G - Green W - White

Wiring M - Screw Terminals C - JST Connector Pressel & Bezel Only BSRCF0000.00



This publication is for general informational purposes only. Product design is subject to change without notice. Actual product colors and finishes may vary.

Copyright © 2020 MAD Elevator Inc.

vantageelevation.com (347) 226-4558 sales@vantageelevation.com