Callouts and labels (top-left plan view):

- 1 1/4 DOOR LAP (SEE NOTE 1)
- APPROXIMATE HEADER LENGTH
- 14
- W
- HEADER SUPPORT BRACKETS
- OPERATOR BACK SUPPORT
- DOOR OPENING
- (4) 3/8-16 TAP
- ALLOW FOR 1" OVERTRAVEL
- BUMPER (BY CAR MANUFACTURER)
- 5/8
- D
- 4 1/8 TYP.
- RETURN LESS THAN 5/8 IN LINE WITH SILL

Callouts (left elevation view):

- DAYLITE
- A (HEADER LENGTH)
- B (NUMBER OF 10" SPACES)
- C
- 10
- 1 1/4" DOOR LAP (SEE NOTE 1)
- 11/16"
- 5/16-18 UNC TAP

Callouts (right section view):

- SPACE REQUIRED FOR OPERATOR ALL OPENINGS 6"
- OPERATOR BACK SUPPORT (CAR MANUFACTURER)
- OPERATOR SUPPORT BRACKET (BY GAL)
- HEADER ASSEMBLY (BY GAL)
- 2
- 2 1/2 X 2 1/2 HEADER ANGLE SAME LENGTH AS G.A.L. HEADER (BY CAR MANUFACTURER)
- 11 1/3"
- 9 1/4"
- 11/16"
- TOP OF DOOR
- ℄ DOOR AND PENDANT BOLTS
- 1 3/8"
- 1/4"
- OVERALL DOOR HEIGHT INCLUDING SHOE BRACKET AND 1/4 BOTTOM CLEARANCE
- 2 1/4" CAR SILL
- 1/4"

Legend (lower right):

- AS SHOWN L.H.
- SYMMETRICALLY OPPOSITE R.H.
- DOOR HEIGHT
- JAMB HEIGHT
- 42" X 84" DOOR OPENING SHOWN

Dimension Table

DIMENSION TABLE (IN)					
DOOR OPENING	A	B	C	D	W
46-48	94	9	2	38	66
43-45	88	8	4	35	60
40-42	82	7	6	32	54
37-39	76	7	3	29	48
34-36	70	6	5	26	42
31-33	64	6	2	23	36
30	58	5	4	20	30

NOTES:

1. PENDANT BOLT AND HEADER HANGER SUPPORT DRILLINGS LOCATED FROM DAYLITE, REGARDLESS OF DOOR LAP SIZE. G.A.L. PREFERS 1 1/4" LAP AT THE LEADING EDGE ONLY.

B	UPDATED COMPANY INFORMATION	10/17/2019	0368
A	INITIAL RELEASE	2/12/2018	0368
REV	DESCRIPTION	DATE	ECN #

8231-MONXT
MONXT SINGLE SPEED CAR DRILLINGS

V. 2019.1
V. 2019.1