

1. PRODUCT AND COMPANY IDENTIFICATION

NAME: GLASS CLEANER
USE: GLASS CLEANER
LABEL BRAND: IND/COM
MSDS # 064158 CODE # 064158

US CHEMICAL, 316 HART STREET, WATERTOWN WI 53094 USA
 MEDICAL EMERGENCY #: 1-866-923-4913 USA
 SPILL EMERGENCY #: 1-800-424-9300 USA
 PRODUCT INFORMATION #: 1-800-558-9566 (8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)
 INTERNET ADDRESS: WWW.USCHEMICAL.COM
 REVIEWED 9-1-10 REVISED 9-1-10 SECTION REVISED: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: CAUTION! CONTENTS UNDER PRESSURE. AEROSOL. TEMPERATURE ABOVE 120°F OR 49°C MAY CAUSE CAN TO BURST. IF FIRE OCCURS, USE EQUIPMENT TO SHIELD OR PROTECT PERSONNEL FROM VENTING OR RUPTURING AEROSOL CANS. MAY BE IRRITATING TO EYES AND SKIN.

PRINCIPLE ROUTES OF EXPOSURE: SKIN, EYES, INHALATION

POTENTIAL ACUTE HEALTH EFFECTS

EYES: MAY BE MODERATELY IRRITATING TO EYES.

SKIN: MAY BE MILDLY IRRITATING TO SKIN.

INHALATION: INHALATION OF MISTS OR VAPORS MAY CAUSE IRRITATION TO NOSE, THROAT, AND MUCOUS MEMBRANES, HEADACHE, DIZZINESS, DROWSINESS AND PULMONARY IRRITATION. SEVERITY DEPENDS ON DEGREE OF EXPOSURE.

INGESTION: MAY CAUSE ABDOMINAL DISCOMFORT, NAUSEA, VOMITING AND DIARRHEA.

MEDICAL CONDITIONS AGGRAVATED: PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTABLE TO IRRITATING EFFECTS.

3. COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS #	% BY WT	LC50/LD50
LIQUEFIED PETROLEUM GAS	68476-86-8	BELOW 10.0	N.AV.
ETHYL ALCOHOL	64-17-5	1.0 - 5.0	N.AV.
2-BUTOXYETHANOL	111-76-2	1.0 - 5.0	N.AV.

STATE RIGHT TO KNOW: THIS PRODUCT CONTAINS:
 WATER/7732-18-5, LIQUEFIED PETROLEUM GAS/68476-86-8, ETHYL ALCOHOL /64-17-5,
 2-BUTOXYETHANOL/111-76-2

4. FIRST AID MEASURES

Page 2 of 4

EYES: IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF DISCOMFORT PERSISTS, GET PROMPT MEDICAL ATTENTION.

SKIN: REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP AND PLENTY OF WATER.

INHALATION: MOVE VICTIM TO FRESH AIR. IF SYMPTOMS DEVELOP, SEEK IMMEDIATE MEDICAL ATTENTION. GIVE ARTIFICIAL RESPIRATION IF PATIENT IS NOT BREATHING.

INGESTION: IF INGESTED, INDUCE VOMITING AND SEEK MEDICAL ATTENTION IMMEDIATELY.

ADMINISTER FIRST AID TREATMENT AS STATED ABOVE, THEN CALL 1-866-923-4913 OR CONTACT PHYSICIAN FOR FURTHER MEDICAL INSTRUCTIONS.

NOTE TO PHYSICIAN: CALL 1-866-923-4913 FOR ASSISTANCE WITH THE MANAGEMENT OF EXPOSURES.

5. FIRE-FIGHTING MEASURES

FLAMMABILITY: NOT REQUIRED TO BE LABELED AS FLAMMABLE AEROSOL AS DESCRIBED BY 16 CFR 1500.3 and 1500.45.

FLAMMABILITY LIMITS (PROPELLANT): SEE SECTION 9.

FLASH POINT: PROPELLANT = BELOW 0°F, CONCENTRATE= ABOVE 200°F

PRODUCTS OF COMBUSTION: SEE SECTION 10.

SUITABLE EXTINGUISHING MEDIA: TO FIGHT FIRE, USE CARBON DIOXIDE, DRY CHEMICAL OR ALCOHOL FOAM.

SPECIFIC HAZARDS: CONTENTS ARE UNDER PRESSURE IN AEROSOL CAN. TEMPERATURE ABOVE 130°F OR 54°C MAY CAUSE AEROSOL CAN TO BURST OR RUPTURE.

SPECIFIC METHODS: COOL CONTAINERS WITH WATER SPRAY TO PREVENT VAPOR PRESSURE BUILD UP. USE EQUIPMENT OR SHIELDING, AS REQUIRED, TO PROTECT PERSONNEL FROM BURSTING, RUPTURING OR VENTING CONTAINERS.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: SEE SECTION 8. PUT ON APPROPRIATE PPE.

SPILL RESPONSE: IF CONTAINERS BEGIN TO LEAK THROUGH PUNCTURE OR DEFECTIVE PACKAGING, ALLOW IT TO DISCHARGE COMPLETELY IN A WELL VENTILATED AREA. WEAR PROTECTIVE EQUIPMENT INCLUDING RUBBER BOOTS. REMOVE SOURCES OF IGNITION. AVOID HEAT, SPARK OR FLAME. KEEP COMBUSTIBLES AWAY! AVOID DIRECT DISCHARGE TO SEWER AND SURFACE WATERS. PUMP TO CONTAINER OR SOAK UP WITH NON-COMBUSTIBLE INERT ABSORBENT MATERIALS. AFTER SPILL COLLECTION, FLUSH AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES. BE CAREFUL AS SPILLS ARE SLIPPERY.

7. HANDLING AND STORAGE

HANDLING: FOLLOW ALL LABEL DIRECTIONS. AVOID HEAT, SPARKS OR OPEN FLAME. INSTRUCT PERSONNEL ABOUT PROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES. AVOID INHALATION, INGESTION AND CONTACT WITH SKIN AND EYES. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. HANDLE CAREFULLY TO AVOID PUNCTURE.

STORAGE: ROTATE STOCK REGULARLY. HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER. KEEP AWAY FROM SPARKS, OR OPEN FLAME. KEEP FROM FREEZING. STORE IN A COOL DRY AREA OUT OF DIRECT SUNLIGHT. KEEP OUT OF CHILDREN'S REACH. KEEP AWAY FROM FOOD AND DRINKING WATER. STORE AS LEVEL 1 AEROSOL (NFPA 30B).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Page 3 of 4

EXPOSURE LIMITS: LIQUEFIED PETROLEUM GAS = 1000 PPM TWA (ACGIH/OSHA)
ETHYL ALCOHOL = 1000 PPM TWA (ACGIH/OSHA)
2-BUTOXYETHANOL = 20 PPM TWA (ACGIH), 50 PPM TWA-SKIN (OSHA)

ENGINEERING CONTROLS: NOT ORDINARILY NEEDED. SPRAY AWAY FROM YOURSELF TO AVOID INHALATION OF MISTS. IF EXPOSURE EXCEEDS LIMITS FOR PEL/TLV, USE A NIOSH APPROVED RESPIRATOR.

PERSONAL PROTECTION

EYES: SAFETY GLASSES WITH SIDE SHIELDS. HAVE AN EYE WASH STATION AVAILABLE.

HANDS: NONE REQUIRED WITH NORMAL USE.

RESPIRATORY: NONE REQUIRED WITH NORMAL USE. AVOID INHALATION OF MIST.

FEET: N.AP.

BODY: N.AP.

9. PHYSICAL AND CHEMICAL PROPERTIES

COLOR: PALE YELLOW

ODOR: FLORAL

pH CONCENTRATE: 10.0

pH @ 2500 PPM SOLUTION: N.AP.

pH @ USE DILUTION: N.AP.

PHYSICAL STATE: LIQUID IN AEROSOL CAN

SPECIFIC GRAVITY: LESS THAN 1.0

VISCOSITY: NON-VISCOUS

BOILING POINT: N.AP.

MELTING POINT: N.AP.

FLASH POINT: SEE SECTION 5.

UEL: 9.5% (FOR PROPELLANT)

LEL: 1.9% (FOR PROPELLANT)

EVAPORATION RATE: N.AV.

ODOR THRESHOLD: N.AV.

VAPOR PRESSURE: 153@130°F PSIG

VAPOR DENSITY: N.AV.

COEFF. OIL/WATER: N.AP.

WATER SOLUBILITY: COMPLETE

OTHER: N.AP.

10. STABILITY AND REACTIVITY

STABLE: YES

CONDITIONS TO AVOID: DO NOT STORE ABOVE 49°C OR 120°F. KEEP AWAY FROM HEAT, DIRECT SUNLIGHT, OPEN FLAMES OR SPARKS. AVOID SPRAYING ON HOT SURFACES. DROPPING MAY CAUSE CONTAINER TO BURST.

MATERIALS TO AVOID: AVOID CONTACT WITH OTHER CLEANING PRODUCTS.

DECOMPOSITION PRODUCTS: FIRE OR MIXING WITH INCOMPATIBLE MATERIALS MAY PRODUCE OXIDES OF CARBON AND OTHER TOXIC OR IRRITATING FUMES.

POSSIBILITY OF HAZARDOUS REACTIONS: N.AP.

11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS: SEE SECTION 2.

CHRONIC EFFECTS: NONE KNOWN. NO REPORTABLE CARCINOGENS, MUTAGENS, SENSITIZERS, SYNERGISTIC MATERIALS, TERATOGENS, OR REPRODUCTIVE TOXINS.

LC50/LD50: N.AV.

TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM

OTHER TOXIC EFFECTS: NONE KNOWN.

12. ECOLOGICAL INFORMATION

Page 4 of 4

NOT AVAILABLE.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL REGULATIONS. CONSULT REGULATORY AGENCIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. DO NOT THROW IN FIRE. DO NOT PUNCTURE OR INCINERATE CONTAINERS. WHEN CONTENTS ARE DEPLETED CONTINUE TO DEPRESS BUTTON UNTIL ALL GAS IS EXPELLED. AEROSOL CYLINDER IS NOT REFILLABLE. GIVE TO A DISPOSAL SERVICE EQUIPPED TO SAFELY DISPOSE OF PRESSURIZED CONTAINERS. PLEASE RECYCLE EMPTY CONTAINER WHENEVER POSSIBLE.

14. TRANSPORT INFORMATION

DOT/TDG: CONSUMER COMMODITY, ORM-D

DOT RQ: N.AP.

IMDG: UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

EPA CERCLA RQ: N.AP.

EPA REGISTERED: NO

OSHA HAZARDOUS: YES

PHOSPHORUS CONTENT: 0.00%

PROPOSITION 65: N.AP.

SARA 311/312 HAZARDS: ACUTE, FIRE, PRESSURE

SARA 313 CHEMICALS: 2-BUTOXYETHANOL

STATE RIGHT TO KNOW: SEE SECTION 3 FOR STATE RTK CHEMICAL NAMES.

TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY.

VOC: 9.70% CALCULATION METHOD USED IS BASED ON CALIFORNIA ARB STANDARD.

16. OTHER INFORMATION

NFPA RATING: HEALTH-1/FLAMMABILITY-1/REACTIVITY-0/SPECIAL HAZARD-N.AP.

HMIS RATING: HEALTH-1/FLAMMABILITY-1/REACTIVITY-0/PERSONAL PROTECTION-SEE 8.0

N.AV. = NOT AVAILABLE N.AP. = NOT APPLICABLE

PREPARED BY: HEALTH AND SAFETY

NOTICE TO READER

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.

8-XMSDS050355