

Power Unit Survey Sheet



Job Name:

Company:

Name:

Phone:

Email:

Submit to:

puquotes@vantageelevation.com

Existing Type	New Preferred Type	Code Compliance	Sourcing Requirements
Submersible Unit	Submersible Unit	ASME A17.1:	
Dry (Belted) Unit	Dry (Belted)	Local AHJ:	

Speed	FPM				
Capacity	lbs	Jack Type	OD (in)	OD (in)	OD (in)
Empty Car Weight	lbs	Existing HP	SPH	Valve Coil Voltage	Telescopic
Empty Static PSI @ LL	PSI				
Working Pressure	PSI	Match HP			
Rise	ft	in	Feedline Diameter		
Line Voltage			Outlet Type		
Outlet hand					

Vantage Standards: Double hinged lid, structural channel feet, isolation pads, pressure gauge, oil sight level gauge, chambered muffler, isolated motor/pump/valve chassis

Options		Quantity	Size / Fitting Type
Low Oil Switch	Electrical Junction Box		Shut-off valve - MR
Low Pressure Switch	Adjustable Overload Pressure Switch		Shut-off valve - Pit
(2) 3/4" NPT Oil Cooler Ports	Down Regulated Valve		
Auto 100° Tank Heater	W&M Suppressor		Isolation coupling - MR
Hot Oil Switch	Sound Isolation Covers (Dry Unit Only)		Isolation coupling - Pit
			Overspeed valve
			Tank Flange
			Jack Flange

Notes