

**SMALL COMPONENTS****FILL IN ALL ITEMS ASSOCIATED WITH THE APPLICATION**

ENGINEERING CONTACT: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

COMPANY: \_\_\_\_\_

ELEV. #: \_\_\_\_\_ H-W #: \_\_\_\_\_

EMAIL: \_\_\_\_\_

PHONE: \_\_\_\_\_

**GENERAL INFORMATION**

- ☐ EMPTY CAR WEIGHT: \_\_\_\_\_
- ☐ CAPACITY: \_\_\_\_\_
- ☐ CAR SPEED: \_\_\_\_\_
- ☐ RAIL SIZE (IN LBS.): \_\_\_\_\_
- ☐ NEMA: \_\_\_\_\_

**SAFETIES**

- ☐ TYPE: ☐ INSTANTANEOUS ☐ FGC
- ☐ COMPENSATION WEIGHT (IF APPLICABLE): \_\_\_\_\_
- ☐ DISTANCE BETWEEN GUIDES: (DBG) \_\_\_\_\_
- ☐ GOVERNOR LOCATION (SHOW ON SKETCH "D")
- ☐ STILE SIZE: \_\_\_\_\_
- ☐ UNDER BEAM HEIGHT: \_\_\_\_\_
- ☐ FILL OUT SHOE AND PLATES SECTION IF ADAPTOR PLATES ARE REQUIRED
- ☐ LOCATION OF SAFETY PICK-UP ARM. FILL OUT DIMENSIONS NOTED IN SKETCH "A"

**GOVERNORS**

- ☐ MOUNTING LOCATION: ☐ STANDARD OVERHEAD MOUNTING ☐ PIT MOUNTED OPTION
- ☐ SHEAVE DIA (ROPE DIA): ☐ 12" (3/8") ☐ 16" (3/8") ☐ 16" (7/16") ☐ 16" (1/2")
- ☐ GOVERNOR PULL-THRU (IN LBS.): \_\_\_\_\_
- ☐ HAND OR LOCATION (SHOW ON SKETCH "D")
- ☐ LIVE SHAFT DIAMETER: ☐ N/A ☐ 12mm ☐ 0.25" ☐ 0.75" ☐ 1.00"
- ☐ ACCESSORIES: ☐ ENCLOSURE ☐ NEMA SWITCH: \_\_\_\_\_
- ☐ RESETTABLE (12" ONLY) ☐ MOUNTING PLATE

**TENSION WEIGHTS**

- ☐ SHEAVE DIA (ROPE DIA): ☐ 12" (3/8") ☐ 16" (3/8") ☐ 16" (7/16") ☐ 16" (1/2")
- ☐ TENSION WEIGHT TYPE: ☐ FRAME ☐ SWING

**SHOES AND PLATES**

- ☐ SHOE TYPE: \_\_\_\_\_ MANUFACTURER: \_\_\_\_\_
- ☐ TEMPLATE (FILL IN ALL DIMENSIONS ON SKETCH "E")

**ROPE GRIPPERS**

- ☐ COMPENSATION WEIGHT (IF APPLICABLE): \_\_\_\_\_
- ☐ ROPING: ☐ 1:1 ☐ 2:1
- ☐ HOIST ROPES: QUANTITY \_\_\_\_\_ SIZE \_\_\_\_\_
- ☐ OUT-TO-OUT OF HOIST ROPES (SEE SKETCH "F" - DIM. "FF"): \_\_\_\_\_
- ☐ LENGTH OF HYDRAULIC HOSE REQUIRED:
- ☐ STANDARD (27")
- ☐ 4'-0" ☐ 5'-0" ☐ 6'-0" ☐ 8'-0" ☐ CUSTOM (UP TO 30'-0"): \_\_\_\_\_

